





# Slitting shears

### **Slitting shears**

- Deformation-free cuts, no distortion
- Top cutting quality, dimensionally accurate positioning
- No setup, immediately ready for operation
- One machine for the most diverse applications thanks to a variety of knives
- Soft grip handle for a safe hold and low-vibration working









TruTool C 160 LiHD 12V

Steel 400 N/mm<sup>2</sup>: 1.6 mm

Steel 600 N/mm<sup>2</sup>: 1.2 mm

Start hole diameter (min.): 8 mm

Smallest radius (L/R): 48/40 mm

Cost-effective all-rounder

without chip clipper

withdrawal from the

■ An open tool for easy

**Technical data** 

### TruTool C 160 with chip clipper LiHD 12V

## TruTool C 200 LiHD 18V

### clipper LiHD 18V

Steel 400 N/mm<sup>2</sup>: 1.6 mm Steel 600 N/mm<sup>2</sup>: 1.2 mm Start hole diameter (min.): 8 mm Smallest radius (L/R): 48/40 mm

- Handy machine with a used in two-handed
- Easy cutting of chip in the
- Ideal for cutting to length and for curved cuts

#### Technical data

- chip clipper that can be operation
- middle of the sheet
- Ideal for interior cutouts and notching

### **Technical data**

Steel 400 N/mm<sup>2</sup>: 2 mm Steel 600 N/mm<sup>2</sup>: 1.5 mm Start hole diameter (min.): 8 mm Smallest radius (L/R): 40/80 mm

- Robust machine without chip clipper
- Open cutting head with wide angles. For easy withdrawal from the
- Ideal for spiral ducts and C, L, U profiles

### TruTool C 250 with chip

(also available as electric version)

### Technical data

Steel 400 N/mm<sup>2</sup>: 2.5 mm Steel 600 N/mm<sup>2</sup>: 1.5 mm Start hole diameter (min.): 15 mm Smallets radius (L/R): 45/80 mm

- Also available as an electric version
- Most powerful model with chip clipper for one-handed operation
- Easy cutting of the chip in the middle of the sheet
- Ideal for interior cutouts and notching



# Staying in shape

Deformation in the sheet is avoided completely with the slitting shears. This means that you achieve cuts that are free of torsion. The sheet surface is not damaged thanks to defined and spiral-shaped rolling of the chip.



Video slitting shears









### One machine different applications?

This is how it works: you purchase a machine and thanks to the cutter variety, then adapt it to the most diverse applications within your sector. For example, when you cut curves or process stainless steel. This not only achieves perfect cutting results and ergonomic operation, but saves a great deal of money as well.



# All in



Depending on the machine type, 2x 12V rechargeable batteries or 2x 18V rechargeable batteries, 1x LG 12-36V recharger and robust TRUMPF Box. Good to know: the CAS battery machines are also available as body only machines (without battery and charger).









### **Shears**

- Chip-free cutting
- Outstanding curvability
- Quick and precise operation. The machine can also be operated upside down
- Minimum strength required thanks to optimal cut geometry
- Cutter can be rotated several times, combined with minor
- Soft grip handle for a safe hold and low-vibration working





#### TruTool S 160 LiHD 12V

#### **Technical data**

Steel 400 N/mm<sup>2</sup>: 1.6 mm Steel 600 N/mm<sup>2</sup>: 1.2 mm Starthole diameter: 28 mm Smallest radius: 16 mm

- Unbeatably small and robust
- Extreme curvability
- For cutting flat sheets, wire mesh and radial cuts

# TruTool S 114 LiHD 12V

#### **Technical data**

Steel 400 N/mm<sup>2</sup>: 1.6 mm Steel 600 N/mm<sup>2</sup>: 1 mm Min. tube diameter: 50 mm Throat depths: 30 mm

- Exceptionally compact design
- Working without interference contours
- Ideal for flush cutting

### Tip

If you need sheet thickness reserves, we recommend our TruTool S 250 LiHD 18V. The powerful shear cuts sheet thicknesses up to 2.5 mm in steel and 2 mm in stainless steel

# Indispensable

For years now, our smallest shear TruTool S 160 has impressed with its handy and ergonomic design. It has an extremely high level of curvability and cuts radii from 16 mm.





# All in



2x 12V rechargeable batteries, 1x LG 12-36V recharger and robust system case. Good to know: the CAS battery machines are also available as body only machines (without battery and charger).







# **Quick and concise**

Are you already familiar with our trimming shear TruTool S 114? You can cut tubes flush with walls using the unique trimming shear. Totally uncomplicated, quick and to an unrivalled high standard. The shear is also ideally suited to smooth roughly cut sheet edges.









Fastening - Seam lockers 11

### **Seam lockers**

- Tight seam joints without force, automatic feed
- Ready for operation in just a few easy steps
- Quick work speed

- Low noise and vibration
- Ready for use directly at the assembly point, even on mounted ducts



TruTool F 300 / TruTool F 300 with 1700 W Motor





TruTool F 140



TruTool F 125



Steel 400 N/mm<sup>2</sup> (min): 0.75 mm Steel 400 N/mm<sup>2</sup> (max): 1.25 mm Smallest inner radius: 150 mm Smallest outer radius: 300 mm



- For Pittsburgh lock seams
- For straight as well as curved ducts
- For flange heights of 9 –
- Automatic adjustment to the sheet thickness

### Technical data

Steel 400 N/mm<sup>2</sup> (min): 0.45 mm Steel 400 N/mm<sup>2</sup> (max): 1 mm Smallest inner radius: 150 mm Smallest outer radius: 300 mm



- For Pittsburgh lock seams
- For straight as well as curved ducts
- For flange heights of 8 –
- Automatic adjustment to the sheet thickness

### Technical data

Steel 400 N/mm<sup>2</sup> (max): 1.4 mm Steel 600 N/mm<sup>2</sup> (max): 0.6 mm Smallest inner radius: 300 mm Smallest outer radius: 500 mm



- For Pittsburgh lock seams
- For straight as well as curved ducts
- For flange heights of 8 –
- Automatic adjustment to the sheet thickness

### Technical data

Steel 400 N/mm<sup>2</sup> (max):1.25mm Max. edge thickness: 5 mm Edge length (max.): 40 mm



- Closing prepared angle and standing seams
- and seam thickness



- Suitable for flange
  - heights of up to 40 mm Manual control of sheet



# All in

The seam lockers need hardly any consumables or accessories. This makes preparation time and running costs negligible. All seam lockers are packaged in practical TRUMPF boxes. For optimum protection.









# The right choice


The flange height of the seam in combination with the sheet thickness determines the correct machine. The TruTool F 140 is the first choice for processing stainless steel. The TruTool F 300 with a 1700 W motor is utilized when you need a powerful drive for continuous use.














■ Minimum preparation time

- Replaces connecting elements such as rivets and screws, for example. Saves costs and avoids interfering contours.
- Low-vibration and quiet operation, free from emissions



During joining, the material properties are unchanged, remain free of oxidation, and the surface structure is not damaged. A form-locking connection joins the upper sheet to the lower sheet, with no welding process. All this without any thermal stress or tension applied to the sheet.

Sealed and tight





### TruTool TF 350 LiHD 18V (also available as electric version)

#### Technical data

Steel 400 N/mm<sup>2</sup>: 3.5 mm Steel 600 N/mm<sup>2</sup>: 2.5 mm Locking power max.: 25 kN Flange height max.: 36 mm

- Connects one or several parts (up to 4 mm), without connecting elements
- Up to 120 joints per minute, unrivalled speed
- Slim, compact machine; ideal for restricted spaces

### This is what our customers say

"The power fastener is extremely easy to handle and immediately ready for operation without a lot of setup. For this reason, and due to the fact that we do not need any additional connecting elements, we can work with it really quickly."

Lippuner Energie- und Metallbautechchnik, Grabs (Switzerland)













# All in



2x 18V rechargeable batteries, 1x LG 12-36V recharger, robust carrying case. Good to know: the CAS battery machine is also available as body only machine (without battery and charger).









14 Battery technology - CAS Electric- and cordless power tools Electric- and cordless power tools 15

Cordless Alliance System

# 1 battery, over 30 brands and 300 machines



Cordless Alliance System (CAS) is a group of leading electric power tool brands, offering you a large selection of powerful machines. You can easily combine the 18V rechargeable batteries and chargers together. The comprehensive system emphasises sustainability and makes it possible for you to greatly reduce the number of rechargeable batteries in your company.



### 100% compatible

Everything works together: 18V battery-powered machines, rechargeable batteries and chargers from any brand. Clear cost advantage thanks to multiple use of existing rechargeable batteries. No matter if it is Li-lon or LiHD technology, 2.0 Ah, 4.0 Ah, 5.2 Ah, 5.5 Ah, 8.0 Ah or 10.0 Ah



### Twice the freedom

CAS means you do not have to depend on cables. In addition you can use machines from different manufacturers.



### Leading rechargeable battery technology

CAS represents a sophisticated rechargeable battery system that you can rely on for standard and special applications.

# One battery for everything. Across manufacturers. 100% compatibility.



## Also of interest:

### The thick sheet nibbler for dismantling work





#### Technical data

Steel 400 N/mm²: 5 mm Steel 600 N/mm²: 3.2 mm Smallest radius: 90 mm Start whole diameter: 41 mm

- 4 cutting directions
- Rotate 360° in 4 x 90°-increments
- Ideal for working in hard-to-reach places and for cutting over edges

As a heating installer you will frequently need to cut containers, tanks or pressure accumulators. For these tasks, we recommend our powerful TruTool N 500. The thick sheet nibbler cuts sheets up to 5 mm and can even be used for renovation work. For example, when removing enameling from bathtubs.

### **Extended warranty**

Extend the standard warranty of your machine to a 5-year warranty. Completely free of charge. The fastest and most convenient method of registering and getting the 5-year warranty is to go to www.trumpf.com/s/warranty-powertools. Our rechargeable batteries have a 3-year guarantee. There's no restriction on charging cycles and no need to register.

Maschine/Machine



Akku/Battery





